Total Safety Solutions

Product advantages:

Injection moulded using a top quality polypropylene copolymer to produce a light, strong and shock resistant product.

- Inner ribbing for additional strength.
- Reinforced fi xing system with safety mechanism.
- Optional: chute moderator to reduce dust and noise.

RUBBISH CHUTE



HOPPER CHUTE



CHUTE MODERATOR



Technical data:

Rubbish chute & Hopper chute

Structure	Polypropylene copolymer. Wall thickness : 5 to 7.5 mm.
Chains	Max. load : 1000 kg/chain. Safety fi xing with trigger release.
Sizes	Inside diameter : 505/380 mm Outside diameter : 540 mm Total length : 1,1 m Working length : 0.85 m Total width : 620 mm.
Weight	Rubbish chute : 7.90 kg. Hopper chute : 8.70 kg.

TSS Trading L.L.C
P.O Box 282691
Dubai, United Arab Emirates
T: +971 4 380 5391
+971 4 338 2701
E: sales@tss-me.com

Visit our website
www.tss-me.com



Fixing system:

WINDOW FIXING FRAME



For walls from 200 to 400 mm thickness. Supports up to 10 rubbish chutes. Electrozinc-coated.

PLATFORM FIXING FRAME



Supports up to 16 rubbish chutes below 40 m high*. Painted grey.

SCAFFOLDING FIXING FRAME



Supports up to 16 rubbish chutes below 40 m high*. Painted grey.

HAND WINCH



with whipple tree for scaffolding and flag fixing frame.